



PAR30 15W LED Lamp



A state of the art LED source and advanced driver, control, and thermal components comprise an integrated LED system with superior lifetime performance. Exceptional optics creates enhanced color uniformity and high lumen output, providing the quality and brightness of light produced by conventional light sources.

quivalent Source	100W Halogen			
Typical Power Consumption	13.5W			
Max. Power Consumption	15W			
.ED source	12*1.0W Cree XPE			
Base/Socket	Medium (E26)			
Beam Spread	Narrow Spot, Narrow Flood, Wide Flood, Very Wide Flood			
Operating Temperature	-20°C to +40 °C			
MOL	3.66", 93mm			
Voltage	AC 120V			
Rated Life	40,000 hours			
Certifications	FC ROHS LISTED			

benefits

Reduced Energy Consumption

Uses up to 90% less power than incandescent bulbs

Long-Lasting:

Lasts up to 10 times as long as compact fluorescents (CFLs) and up to 100 times longer than incandescents.

Durable:

A solid-state device with no moving parts. Contains no fragile filaments or tubes as in incandescent bulbs. The electronic chip is encapsulated in an epoxy substrate, which provides a protective seal against outside or foreign elements. Resistant to heat, cold and shock

More Efficient

Can generate twice the brightness of light (Lumens) at a fifth the wattage of an incandescent

Customizable

Highly customizable (color, beam spread, base, etc.) to fit all lighting needs

No Heat Build Up

Generates little to no heat during operation. This optimizes energy-efficiency (incandescent bulbs emit up to 98 percent of their energy as heat) and reduces demands on air-conditioning.

Mercury Free


No mercury is used in the manufacturing of LEDs.

Specifications		Cool White	
Color Temperature	2000-3500K	4500K+	
Lumen Output	714 Lm	954 Lm	
Efficacy	54 Lm/W	71 Lm/W	
Color Rendering Index (CRI)	80+	70+	



PAR30 15W LED Lamp

Dimensions (in/mm)



Ordering Information

example: NV/PAR30/12.1/WW/NFL/26/CX

product	color	beam spread	base	LED source
NV/PAR30/12.1 - PAR30 12*1W	WW - Warm White CW - Cool White	NSP - Narrow Spot NFL - Narrow Flood WFL - Wide Flood VWFL - Very Wide Flood	26 - E26 (Med.)	CX - Cree XPE

*Note: This product is not designed for use outside, in sealed fixtures, and moist or wet environments.

Beam Spread Key:

Color Key: WW – Warm White: 2000-3500K

VNSP - Very Narrow Spot: <7° NSP - Narrow Spot: 7°-15° SP - Spot: 16°-20°

W - White: 3500-4500K CW - Cool White: 4500K+


NFL - Narrow Flood: 21°-30° FL - Flood: 31°-40° WFL - Wide Flood: 41°-60° VWFL - Very Wide Flood: 61°+

Product Warranty

Nu Vue warrants this LED lamp will be free from defects in material and workmanship and will operate for a period of 1 year under normal operation and when used in accordance with operating guidelines. During the warranty period, if the product fails to perform as described, Nu Vue's entire liability will be limited to the part or repair or replacement of such a defective product. In no event shall Nu Vue be responsible for removal or reinstallation on any product or for the expenses thereof. The above warranty does not apply to, and Nu Vue makes now warranties with respect to products which have been subjected to misuse, neglect, accident, abuse or operated under conditions that deviate from the parameters, established in Nu Vue's applicable specifications; or have been improperly installed, stored, maintained, repaired or altered by anyone other than Nu Vue; or have had their serial numbers or month and year manufacture or shipment removed, defected or altered. This warranty is given only to the original purchaser and may not be assigned or transferred to any other party. It is the purchaser's obligation to retain appropriate documentation that indicates the date of purchase.



9301 Jordan Ave., Unit 105A Chatsworth, CA. 91311 866-996-8883 818-678-9733 sales@nuvuelighting.com



Nu Vue Lighting r is a registered trademark of Nu Vue Lighting L.L.C. c2010 Nu Vue Lighting L.L.C. All Rights Reserved



