

G9 1.1W LED Lamp



A state of the art LED source and advanced driver, control, and thermal components comprise an integrated LED system with superior lifetime performance. Exceptional optics creates enhanced color uniformity and high lumen output, providing the quality and brightness of light produced by conventional light sources.

Lamp Features				
Equivalent Source	20W Halogen			
Typical Power Consumption	1W			
Max. Power Consumption	1.1W			
LED Source	3*0.37 Epistar COG			
Base / Socket	G9			
Beam Spread	Very Wide Flood			
Operating Temperature	-20°C to +40°C			
MOL	48mm			
Voltage	AC 120V			
Rated Life	25,000 hours			
Certifications				

benefits

Reduced Energy Consumption

Uses up to 90% less power than incandescent bulbs

Long-Lasting

Lasts up to 10 times as long as compact fluorescents (CFLs) and up to 100 times longer than incandescents

Durable

A solid-state device with no moving parts. Contains no fragile filaments or tubes as in incandescent bulbs. The electronic chip is encapsulated in an epoxy substrate, which provides a protective seal against outside or foreign elements. Resistant to heat, cold and shock.

More Efficient

Can generate twice the brightness of light (Lumens) at a fifth the wattage of an incandescent

Customizable

Highly customizable (color, beam spread, base, etc.) to fit all lighting needs

No Heat Build Up

Generates little to no heat during operation. This optimizes energy-efficiency (incandescent bulbs emit up to 98 percent of their energy as heat) and reduces demands on air-conditioning

Mercury Free


No mercury is used in the manufacturing of LEDs

Specifications		Cool White
Color Temperature	2700K / 3000K	5700K
Lumen Output	100 Lm / 110 Lm	130Lm
Efficacy	91 Lm/W / 100 Lm/W	118Lm/W
Color Rendering Index (CRI)	80+	70+



G9 1.1W LED Lamp

Dimensions (in/mm) - 13



Net Weight (g) 7

Ordering Information example: NV/G9/3.0.37/WW/VWFL/9/E/C

product	color	beam spread	base	LED source
WW - 300	W27 - 2700K WW - 3000K NW - 4000K	VWFL - VERY WIDE FLOOD	9 - G9	E - EPISTAR
	CW - 5700K	For Opaque cover add (O) to the end of the part number For Clear cover add (C) to the end of the part number		


Beam Spread Key:	Color Key:
VNSP – Very Narrow Spot (<7°) NSP – Narrow Spot (7°-15°) SP – Spot (16°-20°) NFL – Narrow Flood (21°-30°) FL - Flood (31°-40°) WFL – Wide Flood (41°-60°)	W27 - 2700K WW - 3000K NW - 4000K C50 - 5000K CW - 5700K
VWFL – Very Wide Flood (61°+)	

Product Warranty

Nu Vue warrants this LED lamp will be free from defects in material and workmanship and will operate for a period of 3 years under normal operation and when used in accordance with operating guidelines. During the warranty period, if the product fails to perform as described, Nu Vue's entire liability will be limited to the part or repair or replacement of such a defective product. In no event shall Nu Vue be responsible for removal or reinstallation on any product or for the expenses thereof. The above warranty does not apply to, and Nu Vue makes now warranties with respect to products which have been subjected to misuse, neglect, accident, abuse or operated under conditions that deviate from the parameters, established in Nu Vue's applicable specifications; or have been improperly installed, stored, maintained, repaired or altered by anyone other than Nu Vue; or have had their serial numbers or month and year manufacture or shipment removed, defected or altered. This warranty is given only to the original purchase and may not be assigned or transferred to any other party. It is the purchaser's obligation to retain appropriate documentation that indicates the date of purchase.



9718 Variel Ave. Chatsworth,CA 91311 866-996-8883 - 818-882-8955 sales@nuvuelighting.com



Nu Vue Lighting is a registered trademark of Nu Vue Lighting L.L.C. © 2010 Nu Vue Lighting L.L.C. All Rights Reserved

Warnings & Cautions:

- Suitable for use in open fixtures
- Not for use with emergency exit fixtures or emergency lights
- Not for use in enclosed fixtures or insulated
- air-tight (ICAT) recessed down lights
- Turn off power before lamp inspection, installation or removal
- · Do not use where exposed to water or weather
- Not for use outside
- Do not open no serviceable parts inside



