



# G9 3W LED Lamp



A state of the art LED source and advanced driver, control, and thermal components comprise an integrated LED system with superior lifetime performance. Exceptional optics creates enhanced color uniformity and high lumen output, providing the quality and brightness of light produced by conventional light sources.

camp Features	20W Halogop		
Equivalent source	30W Halogen		
Typical Power Consumption	2.7W		
Max. Power Consumption	3W		
LED Source	3*1 Epistar		
Base / Socket	G9		
Beam Spread	Very Wide Flood		
Operating Temperature	-20°C to +40°C		
MOL	49mm		
Voltage	AC 120V		
Rated Life	25,000 hours		
Certifications	FE ROHS USTED CE		

## benefits

### **Reduced Energy Consumption**

Uses up to 90% less power than incandescent bulbs

#### **Long-Lasting**

Lasts up to 10 times as long as compact fluorescents (CFLs) and up to 100 times longer than incandescents

#### **Durable**

A solid-state device with no moving parts. Contains no fragile filaments or tubes as in incandescent bulbs. The electronic chip is encapsulated in an epoxy substrate, which provides a protective seal against outside or foreign elements. Resistant to heat, cold and shock.

#### **More Efficient**

Can generate twice the brightness of light (Lumens) at a fifth the wattage of an incandescent

#### **Customizable**

Highly customizable (color, beam spread, base, etc.) to fit all lighting needs

#### No Heat Build Up

Generates little to no heat during operation. This optimizes energy-efficiency (incandescent bulbs emit up to 98 percent of their energy as heat) and reduces demands on air-conditioning

#### **Mercury Free**


No mercury is used in the manufacturing of LEDs

Specifications		Cool White	
Color Temperature	2700K / 3000K	5700K	
Lumen Output	215 Lm / 235 Lm	280Lm	
Efficacy	72 Lm/W / 78 Lm/W	93 Lm/W	
Color Rendering Index (CRI)	80+	70+	



## G9 3W LED Lamp

## Dimensions (in/mm) - Ø:17



Base G9 Net Weight (g) 10

## Ordering Information

example: NV/G9/3.1/WW/VWFL/9/E/C

product	color	beam spread	base	LED source	
NV/G9/3.1 - G9 3*1W	W27 - 2700K WW - 3000K NW - 4000K CW - 5700K	VWFL - VERY WIDE FLOOD 9 - G9 E - EPI  For Opaque cover add (O) to the end of the		/W - 3000K JW - 4000K	E - EPISTAR he end of the part numbe
		For Clear cover add (C) to the end of the part number			

Your Authorized Nu Vue Lighting Distributor:

Nu Vue Lighting is a registered trademark of Nu Vue Lighting L.L.C.

© 2010 Nu Vue Lighting L.L.C. All Rights Reserved

#### Beam Spread Key: Color Key:

W27 - 2700K WW - 3000K		
C50 - 5000K		
CW - 5700K		
CW 3700K		

## **Product Warranty**

Nu Vue warrants this LED lamp will be free from defects in material and workmanship and will operate for a period of 3 years under normal operation and when used in accordance with operating guidelines. During the warranty period, if the product fails to perform as described, Nu Vue's entire liablilty will be limited to the part or repair or replacement of such a defective product. In no event shall Nu Vue be responsible for removal or reinstallation on any product or for the expenses thereof. The above warranty does not apply to, and Nu Vue makes now warranties with respect to products which have been subjected to misuse, neglect, accident, abuse or operated under conditions that deviate from the parameters, established in Nu Vue's applicable

by anyone other than Nu Vue; or have had their serial numbers or month and year manufacture or shipment removed, defected or altered. This warranty is given only to the original purchase and may not be assigned or transferred to any other party. It is the purchaser's obligation to retain appropriate documentation that indicates the date of purchase.

# Making the world greener.

9718 Variel Ave. Chatsworth,CA 91311 866-996-8883 - 818-882-8955 sales@nuvuelighting.com

#### Warnings & Cautions:

or emergency lights

air-tight (ICAT) recessed down lights

installation or removal

- Do not use where exposed to water or weather
- · Not for use outside
- Do not open no serviceable parts inside



Lighting Output & Life Hours



