



PAR38 13W LED Lamp





A state of the art LED source and advanced driver, control, and thermal components comprise an integrated LED system with superior lifetime performance. Exceptional optics creates enhanced color uniformity and high lumen output, providing the quality and brightness of light produced by conventional light sources.

Lamp Features				
Equivalent Source	90W Halogen			
Typical Power Consumption	11.7W			
Max. Power Consumption	13W			
LED Source	18*.72W Nichia 757			
Base / Socket	Medium (E26)			
Beam Spread	Narrow Flood, Flood			
Operating Temperature	-20°C to +40°C			
MOL	129mm			
Voltage	AC 120V			
Rated Life	25,000 hours			
Certifications	FE ROHS ULISTED CE			

benefits

Reduced Energy Consumption

Uses up to 90% less power than incandescent bulbs

Long-Lasting

Lasts up to 10 times as long as compact fluorescents (CFLs) and up to 100 times longer than incandescents

Durable

A solid-state device with no moving parts. Contains no fragile filaments or tubes as in incandescent bulbs. The electronic chip is encapsulated in an epoxy substrate, which provides a protective seal against outside or foreign elements. Resistant to heat, cold and shock.

More Efficient

Can generate twice the brightness of light (Lumens) at a fifth the wattage of an incandescent

Customizable

Highly customizable (color, beam spread, base, etc.) to fit all lighting needs

No Heat Build Up

Generates little to no heat during operation. This optimizes energy-efficiency (incandescent bulbs emit up to 98 percent of their energy as heat) and reduces demands on air-conditioning


Mercury Free

No mercury is used in the manufacturing of LEDs

Specifications		Cool White	
Color Temperature	2700K / 3000K	5700K	
Lumen Output	1455 Lm / 1550 Lm	1730 Lm	
Efficacy	78 Lm/W / 86 Lm/W	101 Lm/W	
Color Rendering Index (CRI)	80+	70+	



Dimensions (in/mm) - 120



Ordering Information

example: NV/PAR38/18.1/D/WW/FL/26/N

product	color	beam spread	base	LED source
NV/PAR38/18.1/D - PAR38 18*.72 Dimmab	MW - 2700K WW - 3000K NW - 4000K C50 - 5000K C50 - 5700K	NFL - Flood FL - Flood	26 - Medium (E26)	N - Nichia 757

Your Authorized Nu Vue Lighting Distributor:

Nu Vue Lighting is a registered trademark of Nu Vue Lighting L.L.C.

© 2010 Nu Vue Lighting L.L.C. All Rights Reserved

Beam Spread Key: Color Key:

VNSP - Very Narrow Spot (<7°) W27 - 2700K NSP - Narrow Spot (7°-15°) WW - 3000K SP - Spot (16°-20°) NW - 4000K NFL - Narrow Flood (21°-30°) C50 - 5000K FL - Flood (31°-40°) CW - 5700K WFL - Wide Flood (41°-60°)

Product Warranty

VWFL - Very Wide Flood (61°+)

Nu Vue warrants this LED lamp will be free from defects in material and workmanship and will operate for a period of 3 years under normal operation and when used in accordance with operating guidelines. During the warranty period, if the product fails to perform as described, Nu Vue's entire liablilty will be limited to the part or repair or replacement of such a defective product. In no event shall Nu Vue be responsible for removal or reinstallation on any product or for the expenses thereof. The above warranty does not apply to, and Nu Vue makes now warranties with respect to products which have been subjected to misuse, neglect, accident, abuse or operated under conditions that deviate from the parameters, established in Nu Vue's applicable specifications; or have been improperly installed, stored, maintained, repaired or altered by anyone other than Nu Vue; or have had their serial numbers or month and year manufacture or shipment removed, defected or altered. This warranty is given only to the original purchase and may not be assigned or transferred to any other party. It is the purchaser's obligation to retain appropriate documentation that indicates the date of purchase.

Making the world greener.

9718 Variel Ave. Chatsworth,CA 91311 866-996-8883 - 818-882-8955 sales@nuvuelighting.com

Warnings & Cautions:


- Suitable for use in open fixtures
- Not for use with emergency exit fixtures or emergency lights
- · Not for use in enclosed fixtures or insulated air-tight (ICAT) recessed down lights
- Turn off power before lamp inspection, installation or removal
- To obtain actual waterproof effect, lamp must be used in a waterproof fixture
- This product is IP65 Certified and can be used outdoors
- Do not open no serviceable parts inside




Lighting Output & Life Hours









Operating Guidlines:

- Nu Vue dimmable bulbs are designed to work with smooth dimmers and may not dim properly with the following dimmer types:
 - Sensor dimmers
 - Stepping dimmers
 - Remote control dimmers
 - Dimmers with memory function
 - Dimmers with rating of 1000W or above

Dimmer incompatibility may result in flickering, flashing, and/or abnormal light output at certain dimmer levels. If experiencing any of the afore mentioned problems, try the following:

- Check if other high-power-consumption equipment (such as vacuum cleaners, refrigerators, etc.) is being operated on a shared AC line with the dimmable lamps. For best results, operate dimmable lamps on an independent AC line to avoid overloading the line.
- 2. If possible, increase the number of lamps being used with the dimmer in order to raise total power consumption (to over 35 Watts). A power consumption that is too low on an individual dimmer can result in flickering.
- Lamp may not dim immediately after being turned on
- Lamp may emit a bright flash when turned on
- When the dimmer is set at a low level, the lamp may dim further or cease to emit light as a result
 of fluctuations in power (due to power outage or use of electrical devices such as hair dryer
 or microwave)
- For best results, use the power switch to power-off rather than turning the dimmer to its lowest setting
- In the case of shared dimmers, particularly at low settings, light emissions of lamps may be different than when connected to an independent dimmer
- If one or more lamps on a shared dimmer cease to emit light, it may be necessary to set the dimmer to 0% before continuing to use the dimmable function within the emitting range
- Dimmers may emit a soft sound while being tuned



9718 Variel Ave. Chatsworth,CA 91311 866-996-8883 - 818-638-5973 sales@nuvuelighting.com

Your Authorized Nu Vue Lighting Distributor:

